



Spears® Marine Piping Solutions

U.S. Coast Guard Approved

ABS Type Approved



OceanTUFF™

Marine Drainage System

FlameGuard® Fire Sprinkler System
Complies with U.S. Coast Guard



EverTUFF®

**CPVC Hot & Cold Water
Distribution System**



EverTUFF®

**CPVC Marine Sch80
Pressure System**





Features & Benefits



OceanTUFF

Marine Drainage Systems 1-1/2" - 12"

- Complete system of pipe, fittings & one-step cement
- Meets 2010 FTP code annex 1, parts 2 & 5 and may be installed in concealed spaces in accommodation, service and control spaces without meeting the requirements of 46 CFR 56.60-25 (a) (2).
- ABS type approved for black & gray water, vacuum flush sanitary piping, drains, sanitary and vent applications.
- Non-pressure drainage service to 220° F (104° C)
- All CPVC construction in a full assortment of standard DWV patterns including drains, sanitary tees, wyes and P-traps
- Specially formulated, easily-identifiable yellow, one-step solvent cement equal to system pipe & fittings.
- Coast Guard Approved, #164.141/45/0.



EverTUFF

Schedule 40 and 80 CPVC Marine Pipe and Fittings 1/2" - 12"

- Complete system of pipe, fittings, cement & primer
- Meets 2010 FTP code annex 1, parts 2 & 5 and may be installed in concealed spaces in accommodation, service and control spaces without meeting the requirements of 46 CFR 56.60-25 (a) (2).
- ABS type approved for fresh water, sea water, potable water and brine.
- All CPVC construction in a full assortment of standard pressure fitting configurations including specially reinforced threaded adapters and our new GripLoc™ repair fittings for easy system repair.
- Coast Guard Approved, #164.141/45/0



EverTUFF

CPVC Hot & Cold Water Distribution System 1/2"-2"

- Complete system of pipe, fittings & cement for hot & cold water distribution
- Meets 2010 FTP code annex 1, parts 2 & 5 and may be installed in concealed spaces in accommodation, service and control spaces without meeting the requirements of 46 CFR 56.60-25 (a) (2).
- Systems rated to 100 psi @ 180° F (83° C).
- All CPVC construction in a full assortment of standard pressure fitting configurations including specially reinforced threaded adapters and our new GripLoc™ repair couplings for easy system repair.
- Special one-step cement for fast installation
- Coast Guard Approved, #164.141/45/0

ASME B31.3 Bonder training available. For more information contact Spears® Technical Department. (818) 364-1611



SPEARS® MANUFACTURING COMPANY • CORPORATE OFFICE

15853 Olden St., Sylmar, CA 91342 • PO Box 9203, Sylmar, CA 91392

(818) 364-1611 • www.spearsmfg.com

